

Installation Guide

PIG Grippy Adhesive-Backed Absorbent Mat

Step 1 — Surface Preparation

Make sure the surface you want to cover is clean, dry and free of oil and debris before installing PIG Grippy Absorbent Mat.

Step 2 — Application

Place PIG Grippy Absorbent Mat adhesive-side down on a horizontal or vertical surface. Starting at the centre, press down on the mat, working out to the edges and pushing out any air bubbles or creases until it is smooth, flat and securely in place. Depending on the age, condition and smoothness of the surface, prolonged downward force may be required to achieve a uniformly satisfactory bond.

Step 3 — Repositioning and Removal


PIG Grippy Absorbent Mat can be picked up and reapplied as long as the surface is clean and dry. To pick it up, pinch an edge of the PIG Grippy Absorbent Mat with one finger under the bottom tacky side and the other finger on the top absorbent side. Peel up slowly at a 90-degree angle. Using this method will avoid separation of the top and bottom layers, as well as prevent any adhesive residue from being left behind.

NOTE: When using a degreaser to clean the surface prior to placing PIG Grippy Absorbent Mat, rinse the surface thoroughly with water and let dry. Cleaning or polishing products interfere with PIG Grippy Absorbent Mat's adhesion — be sure to wipe surfaces where these products are used with a solvent such as MEK, heptane or lacquer thinner to completely remove them. A second wipe with fresh solvent and a clean cloth may be necessary.

The **stitching on the mat** may begin to fray after an extended period of time or intense use, and may indicate that the mat is due for replacement. Fraying will not affect the absorbency or adhesion of the mat.

Product life varies depending on many factors, including type of use, level of liquid saturation and the frequency of foot and vehicle traffic. PIG Grippy Absorbent Mat is super tough, but it will eventually show wear. Replace the mat when it is worn or when the saturation level approaches the mat edges to avoid liquid seeping out of the mat and under the Grippy backing.

PIG Grippy Absorbent Mat is constructed with a **pressure-sensitive adhesive**, so the heavier the weight of objects on top of the mat, the greater the bond to the surface will become. Inspect the mat regularly to determine how long you can leave it down before removal becomes more difficult.



PIG® Grippy® Absorbent Mat Notice: New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Absorbent Mats should be replaced if they become saturated or show signs of wear or damage.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.



New Pig

Hogs Hill, Watt Place, Hamilton
International Technology Park
Blantyre, Glasgow. G72 0AH

newpig.co.uk • pigpen@newpig.com • 0800 919 900