

PIG Frameless Storm Drain Filter (Medium)

This report is offered as a guide and was developed from information which, to the best of New Pig's knowledge, was reliable and accurate. Due to variables and conditions of application beyond New Pig's control, none of the data shown in this guide is to be construed as a guarantee, expressed or implied. New Pig assumes no responsibility, obligation, or liability in conjunction with the use or misuse of the information.



New Pig

One Pork Avenue
Tipton, PA 16684-0304

newpig.com

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**

Product Performance and Testing

PIG Frameless Storm Drain Filter (Medium)

Part Number	Product Name	Product Size	For Use with Drains
FLT116	PIG Frameless Storm Drain Filter	36"W x 42"L x 17"H	Storm Drains 20" to 30"W and 20" to 36"L; Round Drains 20" to 30" Dia.

Contaminant Removal

Test	Result	UOM	ASTM
Sediment Filter Efficiency	90.8	%	ASTM D-5141
Oil Absorbed	1.29	Gal	ASTM F-726
Heavy metals	None		



Product Data

Test	Result	UOM	ASTM
Flow Rate	400	GPM	ASTM D-8203
Load Capacity	57	lb.	
Sieve Size (AOS)	200/74	Sieve/ Micron	ASTM D-4751
Puncture Resistance	25	lb.	ASTM D-4833
Elongation at Peak MD (%)	36.8	%	ASTM D-4632
Elongation at Break TD (%)	35.3	%	ASTM D-4632
Trapezoid Tear Strength MD	57.98	lb.	ASTM D-4533
Tensile Strength MD	146.7	lb.	ASTM D-4595
Tensile Strength CD	118.3	lb.	ASTM D-4595
Grab Tensile MD	76.7	lb.	ASTM D-4632
Permeability	100.3	GPM/ SF	ASTM D-4491
Fabric Weight	8.50	oz/ sq yd	ASTM D-5261

Data provided is based on ASTM standards. Testing was conducted measuring product performance in center filter pocket.